Working Principle Of Fruit And Vegetable Brush Washing Machine Manufacturing Process

Find latest Working Principle Of Fruit And Vegetable Brush Washing Machine Manufacturing Process, popular food processing machine events and top food processing equipment manufacturers in food manufacturing equipment, Industrial Microwave Oven,Industrial Dryer,Biscuit Making Machine.

Using the slow rotation of the soft brush in the vegetable and fruit brush washing machine and the friction between the fruits and vegetables, the upper part is equipped with two uniform water outlet pipes to continuously discharge water, and the bottom and the middle and lower parts of the side are uniformly distributed with uneven and hard brushes, which can achieve Irregular tumbling in the vegetable brush washer, such as a potato cleaning time is about 5-10 minutes (depending on the cleanliness of the potatoes).

WORKING PRINCIPLE OF VEGETABLE BRUSH WASHER MANUFACTURING PROCESS

	1
1	The hard brush can be used to clean potatoes,
	and the hard brush can remove the skin of the
	potatoes without damaging the meat of the
	potatoes
2	The fruit brush washer machine has two forms
	of forward rotation and reverse rotation. After
	the cleaning, the material can be rotated to
	discharge the material
3	Compared with the market, thisfruit and
	vegetable cleaning machine has a large
	volume, high cleaning efficiency, continuous
	cleaning, and very simple operation
4	After washing, it shows the original color, no
	residual impurities, and effectively removes
	residual pesticides, which can greatly increase
	the sales price of customers.
5	It has the characteristics of large cleaning
	effective volume, high efficiency, water saving,
	continuous cleaning, simple operation and long
	service life.
6	The brush roller material is processed by a
	special process, which is durable and has good
	wear resistance. The fruit brush washer
	machine specifications can be customized
	according to customer requirements.
7	The hair roller material is specially processed
	and rolled by nylon rope with good wear
I and the second	ı

	resistance.
APPLICATION OF VEGETABLE BRUSH V	VASHER PROCESS FOR SALE
	ons and fruits, tubers and medium-round oval each, hawthorn, potato, yam, radish, apple pear ng completely without residue is an indispensable
VEGETABLE AND FRUIT BRUSH WASHE	MANUFACTURING PROCESS
1	First open the top cover of the fruit brush washer, pour a certain amount of fruits and

	vegetables, the number of fruits and vegetables
	should not be excessive, generally below 3
	layers, pass into the water source to moisten
	the fruits and vegetables
2	Start the motor to drive the brush to rotate
3	After the hair roller rotates smoothly, turn on the
	water switch to allow water to wash and
	moisturize the hair roller brush
4	Gradually invest in fruits and vegetables to
	prevent damage to the click load and increase
	damage caused by the concentrated delivery of
	fruits and vegetables
5	After cleaning for about 15 minutes, the
	material door can be opened, the material is
	discharged, and the fruits and vegetables are
	released for drying.
6	After the work is completed on vegetable brush
	washer, rinse the roller brush with water
VEGETABLE BRUSH WASHER CONTROL PANEL	
1	plug in the power supply, turn on the power
	switch
2	After turning on the power switch of the hair
	roller peeling cleaning machine, the power
	indicator light is on
	Choose equipment forward or reverse for fruit
	and vegetable cleaning
3	Clean the fruits and vegetables, click pause
4	Open the spout and pour out the cleaned fruits
	and vegetables
5	Turn off the power after use

3/3